



EF033.1

- Screw connection
- Mounting flange position 1
- 13-14; 23-24 (Contact labelling)
- Suitable for EMERGENCY-OFF

Data

Ordering data

Product type description	EF033.1
Article number (order number)	101006544
EAN (European Article Number)	4250116201242
eCl@ss number, version 12.0	27-37-13-02
eCl@ss number, version 11.0	27-37-13-02
eCl@ss number, version 9.0	27-37-13-02
ETIM number, version 7.0	EC000041
ETIM number, version 6.0	EC000041

Approvals - Standards

Certificates	cULus CCC
--------------	--------------

General data

Standards	EN IEC 60947-5-1 EN IEC 60947-1
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing

Contact labelling	13-14 23-24
Gross weight	22 g

General data - Features

Suitable for EMERGENCY-OFF	Yes
Number of normally open (NO)	2

Mechanical data

Installation instructions	pluggable
Mechanical life, minimum	10,000,000 Operations
Positive break travel	2 mm
Contact opening	3 mm
Note Bounce duration	Bounce duration at an Actuating speed of 100mm/s
Mounting flange position	1

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	0.5 mm ² , rigid 0.5 mm ² , flexible
Cable section, maximum	2.5 mm ² , rigid 1.5 mm ² , flexible
Note (Cable section)	All indications including the conductor ferrules.

Mechanical data - Dimensions

Length	46 mm
Width	10 mm
Depth	60 mm

Ambient conditions

Degree of protection of the switch rooms	IP40
--	------

Degree of protection of clips or terminals	IP20
Ambient temperature	-25_+80
Resistance to shock	110 g / 4 ms
Resistant to vibration	Resistance to vibration: 20 g / 10...200 Hz

Ambient conditions - Insulation values

Rated insulation voltage U_i	400 V
--------------------------------	-------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A
Suitable for low-voltages	$\geq 5 \text{ V} / \geq 3.2 \text{ mA}$
Switching element	Normally open contact (NO)
Switching principle	Slow action
Bounce duration, maximum	5 ms
Switching frequency	1,200 /h
Material of the contacts, electrical	Silver

Pictures

Product picture (catalogue individual photo)




ID: kef03f07

| 51.5 kB | .png | 73.731 x 76.906 mm - 209 x 218 px - 72 dpi

| 407.5 kB | .jpg | 352.425 x 366.889 mm - 999 x 1040 px - 72 dpi

Switch travel diagram




ID: krf--s05

| 18.9 kB | .cdr |

| 1.1 kB | .png | 74.083 x 24.694 mm - 210 x 70 px - 72 dpi

| 29.6 kB | .jpg | 352.778 x 118.181 mm - 1000 x 335 px - 72 dpi

Operating principle



ID: krf--a05

| 19.5 kB | .cdr |

| 189.7 kB | .jpg | 352.778 x 711.2 mm - 1000 x 2016 px - 72 dpi

| 3.7 kB | .png | 74.083 x 149.225 mm - 210 x 423 px - 72 dpi

Schmersal Ltd., Sparrowhawk Close, WR14 1GL Malvern

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 13/04/2023, 10:41